



BAOJI XUAN TAI PIGMENT TECHNOLOGY CO., LTD.
ADD: ROOM, NO. 1608, BUILDING B, WEILAN INTERNATIONAL MANSION,
DAQING 3RD ROAD, LIANHU DISTRICT, XI'AN, SHAANXI, CHINA.
Tel/Fax: +86-029- 88888558 Email: info@xtpigment.com

Material Safety Data Sheet (MSDS)

1. Identification of substance and of the company

Product Name: IRON OXIDE BLUE

BAOJI XUAN TAI PIGMENT TECHNOLOGY CO., LTD.
 Add: ROOM, NO. 1608, BUILDING B, WEILAN INTERNATIONAL MANSION, DAQING 3RD ROAD,
 LIANHU DISTRICT, XI'AN, SHAANXI, CHINA.
 Tel.: +86-029- 88888558

2. Composition/Data on components

Chemical characterization:

Synthetic Iron Oxide Fe₄[Fe(CN)₆]₃·K₄Fe(CN)₆, C. I. Pigment 27 , C I No.77492, CAS. No. 14038-43-8
 HS Code:2821.1000

Compositions		CAS Number
Fe ₂ O ₃	55%	1309-37-1
Pigment Blue	11%	12239-87-1
Water	1%	7732-18-5
SiO ₂	11%	7631-86-9
Al ₂ O ₃	11%	1344-28-1
CaSO ₄	11%	7778-18-9

Dangerous components:

None

3. Hazards identification

*******Emergency Overview*******

May cause mechanical irritation to the eyes, skin and respiratory tract, Irritating gases/fumes may be given off during burning or thermal decomposition.

HMIS Codes: H=1,F=1,R=0,P=0 (0=Minimal, 1=Slight, 2=Moderate, 3=Serious, 4=Severe)

Eyes: Non-irritating to the eyes. Excessive exposure to airborne dust may reduce visibility and /or cause unpleasant deposits.

Skin: will not irritate skin and is not likely to cause allergic skin reaction. Injury to the skin or mucus membranes can occur by direct mechanical action or by rigorous skin cleaning necessary for removal of dust.

Other effects: none known.

Not a hazard in normal industrial use. No harmful effects observed.

The product is not a substance subject to mandatory marking in accordance with the EEC Directive 67/584/EEC

Or amendments.



4. First Aid measures

First aid for skin: In case of skin contact, immediately flush skin with water. Wash clothing before reuse. Call a physician if irritation occurs.

First aid for ingestion: Immediately contact a physician.

First aid for eyes: Flush eyes with plenty of water, lifting lids periodically for at least 15 minutes. Consult a physician if irritation persists.

First aid for inhalation: Remove from dusty area to fresh air. If not breathing give artificial respiration. If breathing is difficult, give oxygen. Call a physician.



5. Fire fighting measures

Product is non-combistible.

Upper Explosive Limit (UEL): Will not explode.

Lower Explosive Limit (LEL): Will not explode.

Fire Fighting Instructions: Firefighters should be equipped with self-contained breathing apparatus to protect against potentially toxic and irritating fumes and smoke inhalation.

Suitable extinguishing media: Material is not combustible. Use extinguishing media suitable for other combustible materials in the area.

Special hazards caused by the material, its combustion products or resultant gases: none

Flash point: Not applicable.

Auto-ignition temperature: Not applicable.

6. Accidental release

Environmental protection conduct: Do not sweep or wash into public stretches of water, sewers or sites of unknown discharge paths.

After spillage/leakage/gas leakage:

Clean up immediately with wetting or absorbent material avoiding dusting

7. Handling and storage

Handling:

Usual precautions for nuisance dust should be observed.

Protection against fire and explosion:

The product is non-flammable

Storage:

Store in roofed places at room temperature. Keep containers tightly sealed.

Flammability Class: not applicable

8. Exposure controls/personal protection

Additional notes for design of plant equipment:

No further details, see sec. 7

Components with workplace-related limits to be monitored:

Designation	%	Type of data	Unit
Nuisance dust	100	MAK	6 mg/m ³
		TLV/TWA(USA)	10 mg/m ³

Personal protection equipment:

Respiratory protection:

An appropriate dust filter has to be used if a breathable dust is liberated.



9. Physical and chemical properties

form: Powder

colour: Blue

odour: odourless

Change in physical state

Thermal Decomposition:

Value/Area	Unit	Method
n.a.	°C	Lit.

Flash point: not flammable

Flammable properties: The product is not flammable under standardized conditions.

Explosion risks: The product is not explosive

Vapour pressure:

n.a. mbar

Density: (20°C) 4,1

g/cm³ DIN/ISO 787 part 10 B

Solubility in water: (20°C) <0,5

% DIN/ISO 787 part 3

PH-Value: (at 100 g/l H₂O) ca.3.5~7

DIN/ISO 787 part 9



10. **Stability and reactivity**

Hazardous Polymerization: Will not occur.
Stability: Stable Material.
Incompatibilities: None known.
Instability conditions: None known.
Decomposition temperature: Greater than 120 C.
Decomposition products: None known.

11. **Toxicological Information**

Because of experiences with the product mentioned, there are no recognizable hazards for human beings, If it is correctly used and applied.

12. **Ecological information**

Avoid infiltration into waster drainings or soil.

13. **Disposal considerations**

Product:
 Dispose in accordance with federal, state and local regulations.
Waste Code No.:
 Check re-use as alternative.
Contaminated packages and containers:
 Emptied, but contaminated packages and containers may be recycled.
Waste Code No.: 18715 (Germany)

14. **Transport information**

International:

Land transport:	ADR/RID/GGVS/GGVE:	Not Regulated
Sea transport:	IMDG/GGV See UN-No.:	Not Regulated
Air transport:	ICAO/IATA UN/ID-No.:	Not Regulated

U.S.	D.O.T.Classification:	Not Regulated
CANADA	Transport of dangerous goods:	Not Regulated

DOT Shipping Name: None

Technical Shipping Name: Inorganic Oxide

DOT Hazardous Classification: Non-Regulated. This product is not classed as a dangerous substance under the Classification, Packaging and Labeling of Dangerous Goods Act.

DOT Hazard Class: Non-Regulated.

DOT Identification Number: None

DOT Labels required: None

DOT Placards required: None. No specific transportation precautions required.

UN Class: None.

UN/NA Number: None.





BAOJI XUAN TAI PIGMENT TECHNOLOGY CO., LTD.
ADD: ROOM, NO. 1608, BUILDING B, WEILAN INTERNATIONAL MANSION,
DAQING 3RD ROAD, LIANHU DISTRICT, XI'AN, SHAANXI, CHINA.
Tel/Fax: +86-029- 88888558 Email: info@xtpigment.com

15. Regulatory information

Labeling according to EEC Directives: Not Regulated.

SARA

SARA 312:

Health: Immediate (Acute):	No*	Fire:	None
Delayed (Chronic):	No**	Reactivity:	None
		Sudden release of pressure:	None

Not an acute hazard, however may cause irritation due to abrasiveness.

These products are not classified as Carcinogens by the National Toxicology Program, the International Agency for Research on Cancer or the Occupational Safety and Health Administration. We do not know of any chronic health effect from these products. The finished pigment is a fine powder and may increase the risk of respiratory and skin disorders aggravated by dust.

The product is not a substance subject to mandatory marking in accordance with the EEC Directive 67/548/EEC or amendments.

Water risk class: WGK 0 (Self-assessment, acc. to § § 7a 19,19a-1 of German Water Utilization Act (WHG))

16. Further information:

HMIS Codes: H=1,F=1,R=0,P=0 (0=Minimal, 1=Slight, 2=Moderate, 3=Serious, 4=Severe)

Vertical markings at left margin denote alterations of previous issue.

The information contained herein is based on the present state of our knowledge, but without liability, which is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of the manufacturer. The data on this sheet relates only to the specific material designated herein. It may not be valid for this material responsibility to verify suitability and completeness of this information for their own particular use. The manufacturer assumes no legal responsibility for use or reliance upon these data.

Department issuing this data sheet: Product safety department

